



Metal Gaskets (Flat & Serrated Types)

Metal flat seals are used to seal connections in stationary locations, such as components.

By sealing the gaps between the connections, they prevent leakage of fluid passing through the interior and contamination by foreign

A variety of shapes, thicknesses, and materials are available to suit the connection.

Parts No.	SIZE	UFC-1660
855-005-1002	7.1x0.3x1.29	Orifice Seal
859-018-6001	24.28x21.23x0.75	Valve Thin style
859-018-6002	6.60x3.56x0.75	Sensor Seal
859-018-6003	21.75x18.69x0.75	Fitting Seal Thin
859-018-6004	18.19x15.14x0.75	Fitting Seal Thin
859-018-6005	26.47x21.23x0.75	Valve Thick style
859-018-6006	8.89x3.56x0.75	Sensor Seal
859-018-6007	21.74x16.66x0.75	Inlet Thick Seal
859-018-6008	16.26x10.06x0.75	Outlet Seal Thick
859-018-6009	19.94x16.89x0.75	UFC-85xx Fitting Seal
859-018-6010	33.35x29.08x0.75	Fitting Seal Thin
859-018-6011	32.74x27.69x0.75	Fitting Seal Thin
908928-004	27.15x19.30x1.0	TYLAN FC-2900 MOI VALUE Seal
908928-005	23.8x17.20x1.0	MOI Fitting Seal
908928-006	7.5x2.1x1.0	TYLAN
499-003-008	27.15x19.30x1.0	Fitting Seal Thin

Other sizes are also available